

1014PSEI /1016PSEI



Stainless Steel 304 or 316 explosion proof Thermocouple head, provided with IECEx certification, IP66/68 rating. The connection head accommodates an elliptical block or transmitter 2" (50mm) in diameter.



- EXPLOSION-PROOF CERTIFIED
- IP66/68 CERTIFIED
- WIDE SELECTION OF CONDUIT SIZES
- OPTION FOR A CUSTOMIZED SS HALF MOON NAME PLATE

Material of Construction : S.S. 304/S.S. 316

Certification : IECEx

Connections: : ½" NPT, ¾" NPT, M20x1.5P , **M24 x 1.5**

Surface Finishing: : S.S.

"O" Ring : Buna "N"

Weight: : 1.22 KG (2.7lbs)

Accessories: : Terminal Block (Ceramic or Bakelite)



Ex db IIC Gb Ta =20°C to 125°C IP66/68

Ex tb IIIC Db Ta= -50°C to 125°C IP66/68

Model	T1 Tread	T2 Tread	Description
1014PSEI-01	3/4"NPT X	1/2" NPT	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-02	1/2" NPT X	1/2" NPT	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-03	3/4"NPT X	3/4" NPT	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-04*	1/2" NPT X	3/4" NPT	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-05*	3/4"NPT X	M20 X1.5	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-06*	1/2" NPT X	M20 X1.5	S.S. 304 Explosion Proof Thermocouple head IECEx P66/68
1014PSEI-07	3/4"NPT X	M24 X1.5	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-08	1/2" NPT X	M24 X1.5	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-11	M20 X1.5 X	1/2" NPT	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-12*	M20 X1.5 X	1/2" NPT	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-13*	M20 X1.5 X	M20 X1.5	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-14*	M20 X1.5 X	M24 X1.5	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-15*	M24 X1.5 X	3/4" NPT	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-16*	M24 X1.5 X	1/2" NPT	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-17*	M24 X1.5 X	M20 X1.5	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68
1014PSEI-18*	M24 X1.5 X	M24 X1.5	S.S. 304 Explosion Proof Thermocouple head IECEx IP66/68

Model	T1 Tread	T2 Tread	Description
1016PSEI-01	3/4"NPT X	1/2" NPT	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-02	1/2" NPT X	1/2" NPT	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-03	3/4"NPT X	3/4" NPT	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-04*	1/2" NPT X	3/4" NPT	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-05*	3/4"NPT X	M20 X1.5	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-06*	1/2" NPT X	M20 X1.5	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-07	3/4"NPT X	M24 X1.5	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-08	1/2" NPT X	M24 X1.5	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-11	M20 X1.5 X	1/2" NPT	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-12*	M20 X1.5 X	1/2" NPT	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-13*	M20 X1.5 X	M20 X1.5	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-14*	M20 X1.5 X	M24 X1.5	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-15*	M24 X1.5 X	3/4" NPT	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-16*	M24 X1.5 X	1/2" NPT	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-17*	M24 X1.5 X	M20 X1.5	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68
1016PSEI-18*	M24 X1.5 X	M24 X1.5	S.S. 316 Explosion Proof Thermocouple head IECEx IP66/68

* THESE PRODUCTS

UPON REQUEST WITH EXTRA LEAD TIME

no gaps between the numbers)