

1114PSET /1116PSET



Stainless Steel 304 or 316 explosion proof Thermocouple head, provided with ATEX certification, IP66 rating. The connection head accommodates an elliptical block or transmitter 2" (50mm) in diameter.



- EXPLOSION-PROOF CERTIFIED
- IP66 CERTIFIED
- WIDE SELECTION OF CONDUIT SIZES
- OPTION FOR A CUSTOMIZED SS HALF MOON NAME PLATE

Material of Construction : S.S. 304/S.S. 316

Certification : ATEX

Connections: : 1/2" NPT, 3/4" NPT, M20x1.5P , M24 x 1.5

Surface Finishing: : S.S.

"O" Ring : VITON

Weight: : 1.22 KG (2.7lbs)

Accessories: : Terminal Block (Ceramic or Bakelite)



II 2G Exdb IIC Gb Ta = -16°C to 125°C IP66

II2D Ex tb IIIC Db Ta= -16°C to 125°C IP66

Model	T1 Tread	T2 Tread	Description
1114PSET-01*	3/4"NPT X	1/2" NPT	Explosion Proof Thermocouple head ATEX IP66
1114PSET-02*	1/2" NPT X	1/2" NPT	Explosion Proof Thermocouple head ATEX IP66
1114PSET-03*	3/4"NPT X	3/4" NPT	Explosion Proof Thermocouple head ATEX IP66
1114PSET-04*	1/2" NPT X	3/4" NPT	Explosion Proof Thermocouple head ATEX IP66
1114PSET-05*	3/4"NPT X	M20 X1.5	Explosion Proof Thermocouple head ATEX IP66
1114PSET-06*	1/2" NPT X	M20 X1.5	Explosion Proof Thermocouple head ATEX IP66
1114PSET-07*	3/4"NPT X	M24 X1.5	Explosion Proof Thermocouple head ATEX IP66
1114PSET-08*	1/2" NPT X	M24 X1.5	Explosion Proof Thermocouple head ATEX IP66
1114PSET-11*	M20 X1.5 X	1/2" NPT	Explosion Proof Thermocouple head ATEX IP66
1114PSET-12*	M20 X1.5 X	1/2" NPT	Explosion Proof Thermocouple head ATEX IP66
1114PSET-13*	M20 X1.5 X	M20 X1.5	Explosion Proof Thermocouple head ATEX IP66
1114PSET-14*	M20 X1.5 X	M24 X1.5	Explosion Proof Thermocouple head ATEX IP66
1114PSET-15*	M24 X1.5 X	3/4" NPT	Explosion Proof Thermocouple head ATEX IP66
1114PSET-16*	M24 X1.5 X	1/2" NPT	Explosion Proof Thermocouple head ATEX IP66
1114PSET-17*	M24 X1.5 X	M20 X1.5	Explosion Proof Thermocouple head ATEX IP66
1114PSET-18*	M24 X1.5 X	M24 X1.5	Explosion Proof Thermocouple head ATEX IP66

Model	T1 Tread	T2 Tread	Description
1116PSET-01*	3/4"NPT X	1/2" NPT	Explosion Proof Thermocouple head ATEX IP66
1116PSET-02*	1/2" NPT X	1/2" NPT	Explosion Proof Thermocouple head ATEX IP66
1116PSET-03*	3/4"NPT X	3/4" NPT	Explosion Proof Thermocouple head ATEX IP66
1116PSET-04*	1/2" NPT X	3/4" NPT	Explosion Proof Thermocouple head ATEX IP66
1116PSET-05*	3/4"NPT X	M20 X1.5	Explosion Proof Thermocouple head ATEX IP66
1116PSET-06*	1/2" NPT X	M20 X1.5	Explosion Proof Thermocouple head ATEX IP66
1116PSET-07*	3/4"NPT X	M24 X1.5	Explosion Proof Thermocouple head ATEX IP66
1116PSET-08*	1/2" NPT X	M24 X1.5	Explosion Proof Thermocouple head ATEX IP66
1116PSET-11*	M20 X1.5 X	1/2" NPT	Explosion Proof Thermocouple head ATEX IP66
1116PSET-12*	M20 X1.5 X	1/2" NPT	Explosion Proof Thermocouple head ATEX IP66
1116PSET-13*	M20 X1.5 X	M20 X1.5	Explosion Proof Thermocouple head ATEX IP66
1116PSET-14*	M20 X1.5 X	M24 X1.5	Explosion Proof Thermocouple head ATEX IP66
1116PSET-15*	M24 X1.5 X	3/4" NPT	Explosion Proof Thermocouple head ATEX IP66
1116PSET-16*	M24 X1.5 X	1/2" NPT	Explosion Proof Thermocouple head ATEX IP66
1116PSET-17*	M24 X1.5 X	M20 X1.5	Explosion Proof Thermocouple head ATEX IP66
1116PSET-18*	M24 X1.5 X	M24 X1.5	Explosion Proof Thermocouple head ATEX IP66

* THESE PRODUCTS

UPON REQUEST WITH EXTRA LEAD TIME

no gaps between the numbers)