


NEEDLE VALVE-FNVS



. HAVI Forged Needle Valve series has a Forged Body with Integral as well as Screwed Bonnet design with PTFE and Graphoil packing

The Valve gives a leak proof service for pressures upto 6000 psi. Valves are available in straight as well as angle configurations.

OPENIGS

Part No.(HAVI)	Quantity	E1	E2	NPTF	NPTF2	Thread (P) NPT	Thread (P) NPT2	A	O-Orifice
NVFS-4T	<input type="text"/>	1/4"T	1/4"T					56	4
NVFS-6T	<input type="text"/>	3/8"T	3/8"T					56	4
NVFS-8T	<input type="text"/>	1/2"T	1/2"T					56	4
NVFS-4F	<input type="text"/>			1/4"	1/4"			56	4
NVFS-6F	<input type="text"/>			3/8"	3/8"			56	4
NVFS-8F	<input type="text"/>			1/2"	1/2"			68	4
NVFS-4NM	<input type="text"/>					1/4"	1/4"	56	4
NVFS-6NM	<input type="text"/>					3/8"	3/8"	56	4
NVFS-8NM	<input type="text"/>					1/2"	1/2"	68	4

FEATURES

Product Feature -

Working Pressure of 6000 psi

Valves tested in accordance with BS EN 12266-4.

Non rotating tip design to eliminate rotation between Seat and Tip.

Available in Straight, angle and cross configuration.

Stainless Steel Construction with options of packing for high temperature applications.

Colour coded dust caps for identification of Valve type.

100% Factory Tested.

Metal to Metal Seating.

Thread Rolled and Burnished Stem.

Differential hardened tip for life enhancement.